



JDD-PA NYLON 6.6 EXPANDABLE SLEEVING

It is designed for applications with intensive abrasion and frequent contact with hard surfaces. The smooth, low-friction surface prevents snagging and damage during routing and maintenance of cable harnesses.

It is used where cables are movable, pass through brackets or edges, or are exposed to oils and technical fluids, making it suitable for transportation, aerospace, and special-purpose systems.



TECHNICAL DATA:

- ✔ Material: Polyamide 6.6
- ✔ Working temperature: -60°C~ +160°C
- ✔ Melting point: 256 ± 5°C
- ✔ Color: Black and grey
- ✔ Cutting tool: Hot knife
- ✔ Approval: RoHS, REACH, Halogen Free

Diameter	Article number	Minimum expansion	Maximum expansion	Packing quantity
3 mm	PA-003	1 mm	6 mm	1000 m
6 mm	PA-006	3 mm	9 mm	500 m
8 mm	PA-008	5 mm	16 mm	350 m
10 mm	PA-010	7 mm	19 mm	350 m
12 mm	PA-012	8 mm	24 mm	300 m
16 mm	PA-016	10 mm	27 mm	250 m
19 mm	PA-019	14 mm	30 mm	200 m
25 mm	PA-025	18 mm	35 mm	200 m
32 mm	PA-032	20 mm	50 mm	150 m
38 mm	PA-038	30 mm	60 mm	100 m
45 mm	PA-045	35 mm	75 mm	100 m
50 mm	PA-050	40 mm	80 mm	100 m
64 mm	PA-064	45 mm	105 mm	100 m
76 mm	PA-076	64 mm	120 mm	100 m

