

- 3,600 Cycles\*
- Outstanding Protection Against Abrasion
   & Cut-Through
- Resists Gasoline,
  Engine Chemicals,
  & Cleaning Solvents
- Does Not Trap Heat Or Humidity
- Resists Fraying When Cut With Scissors







CLEAN CUT HD (CCH) is perfect for heavy duty applications where there is no access to a hot knife.

This dual monofilament sleeve is constructed with 10 mil polyethylene terephthalate (PET) and 15 mil nylon 6-6 polyamide monofilament yarns for superior strength. For an extra level of protection, a resin coating is applied to offer improved abrasion, cut, and fray resistance. The open-weave construction expands to fit several application shapes and sizes, and also makes this sleeving highly flexible and resistant to trapping moisture, heat and humidity.

Clean Cut HD is commonly used in military, marine, and industrial applications where additional abrasion and moisture protection is needed.





Nominal	Part	Wall Thickness	Expansion Range		Standard Spool Put-Ups		Available	Lbs/
Size	#		Min.	Max.	Bulk Spool	Shop Spool	Colors	100′
1/8"	CCH0.13BK	.0285"	1/8"	1/4"	1,000′	100′	Black (BK)	0.28
1/4"	CCH0.25BK	.0285"	1/8"	3/8"	1,000′	100′	Black (BK)	0.42
3/8"	CCH0.38BK	.0285"	1/4"	1/2"	500′	100′	Black (BK)	0.80
1/2"	CCH0.50BK	.0285"	3/8"	3/4"	500′	100′	Black (BK)	1.06
3/4"	CCH0.75BK	.0285"	3/4"	1 1/4"	250′	75′	Black (BK)	1.60
1"	CCH1.00BK	.0285"	1″	1 1/2"	250′	50′	Black (BK)	1.71
1 1/4"	CCH1.25BK	.0285"	1 1/4"	2 1/4"	250′	50′	Black (BK)	2.02
1 1/2"	CCH1.50BK	.0285"	1 1/2"	2 1/2"	200′	50′	Black (BK)	2.70
2"	CCH2.00BK	.0285"	2″	3 1/4"	100′	25′	Black (BK)	3.36

1-973-300-9242 www.techflex.com

.2	Abrasion Resistance										
m	630	950	2,500	*3,600	4,400	8,500	13,000				
	HIGH				EXTREMELY HIGH						

