

Mechanical characteristics
cables

interface dimensions acc. to assembly code
 centre conductor
 outer conductor
 mating life

Components
 centre contact
 outer contact
 bayonet
 spring washer
 other metal parts
 insulator
 gasket

Electrical characteristics
 impedance
 frequency
 return loss

working voltage
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental
 operating temp.
 protection class
 RoHS compliant

Mechanische Eigenschaften
Kabel

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen

Bauteile
 Innenkontakt
 Außenkontakt
 Bajonett
 Federscheibe
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften
 Wellenwiderstand
 Frequenz
 Rückflussdämpfung

Betriebsspannung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung
 Betriebstemperatur
 Schutzklasse
 RoHS konform

G37 : 2,7/7,3 AF, 2,7/7,3 CF, 213CRT7 LOW LOSS, 7810A, 9913, C2FCP, C2FP, CNT-400, EC 400, HPF 400, LMR-400, MRC 400 AFB, TZC 500 32, SPEEDFOAM 400 HFJ, WBC-400, WCX400
 G42 : 02Y (St) C (St) H 2,6/7,3 AF, 213RT5, 9914, H 1000, H2000, RT 50/20

Ⓐ G55: 9913F, MRC 400 Flex
 RG-213/U
 RG-214/U

IEC 61169-8
 D11
 solder / Löt
 clamp / Klemm
 >500



Materials / Material
 brass / Messing
 brass / Messing
 zinc diecast / Zinkdruckguss
 copper alloy / Kupferlegierung
 brass / Messing
 PTFE
 silicone, NBR

Finish / Oberfläche
 Cu1Ni2Au0.8
 Cu2Ni5
 Zn/Cu6Ni6
 Cu2Ni5
 CuSnZn3

50 Ω
 0 - 4 GHz Ⓐ
 typ.: 1 GHz -30 dB ; 2 GHz -26 dB ; 3 GHz -21 dB

≤ 500 V_{eff} / 50 Hz
 1,5 kV_{eff} / 50 Hz
 ≥ 5 GΩ
 ≤ 20 mΩ
 ≤ 5 mΩ

Ⓐ 2011/65/EU

a	25485	21.01.2014	GB	Name/ name gez./ drawn 20.12.2010 GB	Datum/ date Name/ name GB	Gewicht/ weight (g)			
				Name/ name gepr./ appr. 23.12.2010 PU	Datum/ date Name/ name PU	ca./approx.			
				Maßstab/ scale 1:1			Benennung/ title BNC Angle Plug BNC-Kabelwinkelstecker		
				Untert./ doc. type K			Zeichnungsnr./ drawing no. J01000B1195		
				Ersatz für/ replaces J01000A0029; J01000A1195					
									
				 Maße/ dimensions: mm					
				Original : DIN A4					
				Blatt/ sheet 1 von/ of 1					