



Meets More Specs and Standards

FLEXO ULTIMATE FR (UFR) sleeving is the ultimate choice for high tech applications such as aerospace, telecom, and military where flame retardance and durability are a top priority. All of the same great features of our Flexo FR with new additional engineering to have it meet more specs and more standards.

The high expansion rate of UFR makes for easy and efficient installs. Chemical resistant, high temperature stable, and abrasion resistant. Ultimate FR — when “yes” is the only answer!

- **Expands Up To 150%**
- **Resists Gasoline And Engine Chemicals**
- **Easy To Install**
- **Cut And Abrasion Resistant**
- **Halogen Free**
- **Cuts Cleanly With Hot Knife**



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/4"	UFR0.25TB	1/8"	7/16"	1,000'	200'	Black w/White Tracer (TB)	0.26
3/8"	UFR0.38TB	1/4"	5/8"	500'	125'	Black w/White Tracer (TB)	0.57
1/2"	UFR0.50TB	3/8"	15/16"	500'	100'	Black w/White Tracer (TB)	0.72
3/4"	UFR0.75TB	1/2"	1 1/4"	250'	75'	Black w/White Tracer (TB)	1.07
1"	UFR1.00TB	5/8"	1 3/4"	250'	65'	Black w/White Tracer (TB)	1.34
1 1/4"	UFR1.25TB	3/4"	1 7/8"	250'	50'	Black w/White Tracer (TB)	1.60
3 End Construction							
1/4"	UFR30.25TB	1/8"	3/4"	1,000'	200'	Black w/White Tracer (TB)	0.39

