



OPERATING & ASSEMBLY INSTRUCTION

NAC3MPX-TOP & NAC3MPX-WOT-TOP powerCON® TRUE1 TOP | APPLIANCE INLET

OPERATING INSTRUCTION


Application:

The powerCON TRUE1 system is certified as a connector with breaking capacity according IEC 60320, VDE 0625. It is intended for use as an appliance coupler and interconnection coupler. It serves to supply power to an appliance and from an appliance to other equipment. To be installed by qualified person only.

CONNECTOR ASSIGNMENT:


APPLIANCE INLET

NAC3MPX-TOP
NAC3MPX-WOT-TOP
Power IN ▶




APPLIANCE OUTLET

NAC3FPX-TOP
NAC3FPX-WOT-TOP
NAC3FPX-ST-TOP
Power OUT ◀




APPLIANCE INLET / OUTLET ▶ Combination


NAC3PX-TOP
Power IN ▶




Power OUT ◀





NAC3FX-W-TOP
(Connector)



NAC3MX-W-TOP
(Plug connector)



NAC3FX-W-TOP
(Connector)




NAC3MX-W-TOP
(Plug connector)

powerCON TRUE1 TOP line is full backward compatible with the preceding powerCON TRUE1 products.


UL50E environmental rating

Enclosure Type 4 when installed with sealing cover SCNAC-MPX and cover closed or when mated with cord connector NAC3FX-W-TOP.

ASSEMBLY INSTRUCTION




NAC3MPX-WOT-TOP



NAC3MPX-TOP


Flat tabs for 1/4" FASTON®

WIRING



Attention:
Tightening torque
 $M_A = 40 \text{ Ncm}$.

Panel Cutout (Rear Side)



Find more details of powerCON TRUE1 TOP on www.neutrik.com.