

für Kabel / for cable: G23 5092 1/2"-Hiflex Eupen
FSJ4-50B Andrew
HFSC 12D LS Cable
HPL 50-1/2SF Acome
RFF 1/2"-50 Draka
SCF 12-50 J RFS
Flexline 1/2" S Leoni
Sucofeed_1/2_HF Huber+Suhner



Serie 7/16
Series 7/16



Serie N
Series N

Bestell-Nr. / P/N	Kurzbezeichnung / short name
J01020A0098	N-Kabelstecker / N straight plug
J01021A0156	N-Kabelbuchse / N straight jack
J01120B0073	7/16-Kabelstecker / 7/16 straight plug
J01121B0114	7/16-Kabelbuchse / 7/16 straight jack
N00091A0004	Absetzwerkzeug / cutting tool
N00099A0001	Ersatzklingen / spare cutting blades


Achtung: Die Klingen sind sehr scharf. Das Werkzeug ist vorsichtig zu handhaben. Es wird empfohlen, Arbeitshandschuhe zu tragen.

Attention: The blades are very sharp. The tool is to be handled with care. It is recommended to wear working gloves.

Empfohlene Werkzeuge / recommended tools:

- Absetzwerkzeug / cutting tool (N00091A0004)
- Messer / knife (N00080A0003)
- 2 Gabelschlüssel SW24 / 2 spanner 24af (15/16")
- 1 Gabelschlüssel SW22 / 1 spanner 22af (7/8")
- 1 Gabelschlüssel SW7 / 1 spanner 7af (9/32")
- 1 Gabelschlüssel SW17 / 1 spanner 17af (11/16")
- Innensechskant 2 / hexagon socket 2 (5/64")
- Innensechskant 2,5 / hexagon socket 2,5 (3/32")
- Schraubendreher 0,8x4 / screwdriver 0,8x4

Anbindemöglichkeit
Hole for tie-on



Feinjustierung (Schnitttiefe)
für Kabeltoleranzen.
Voreingestellt auf Kabel
RFF 1/2"-50
*Fine adjustment (cutting
depth) for cable tolerances.
Pre-adjusted for cable
RFF 1/2"-50*

Innensechskant 2
Hexagon socket 2
(5/64")

Bei Klingenwechsel
Anzugsmoment max. 50 Ncm
(Klinge muss frei laufen)
*When changing
the cutting blade
torque max. 50 Ncm
(blade must
turn freely)*

Gabelschlüssel SW7
Spanner 7af (9/32")

Innensechskant 2,5
Hexagon
socket 2,5 (3/32")

