

E-DAT industryIP67 8(8) Stecker / Plug

Montageanweisung / Assembly Instruction



① Lieferumfang / Scope of delivery
Stecker / Plug 130906-03-E

②

ca. 40 mm

SF/UTP

S/FTP

③

Paarfolie entfernen /
Remove foil

SF/UTP

S/FTP

S/FTP

④

Anschlussbelegung PIN assignments		
Farbcode T568...		RJ45 PIN No.
A	B	
W-G	W-O	1
G	O	2
W-O	W-G	3
BL	BL	4
W-BL	W-BL	5
O	G	6
W-BR	W-BR	7
BR	BR	8

⑤

1

8

⑥

⑦

⑧

⑨ Steckereinsatz in den Steckerkörper einrasten / Snap in plug insert into plug body

⑩ Crimpzange / Crimp tool 130907-E

⑪

⑫

E-DAT industry IP67 8(8) Stecker / Plug

Montageanweisung / Assembly Instruction



<p>13 Crimpen / Crimp</p>	<p>14</p>	<p>15 Schirmgeflecht abschneiden / cut off braid</p>										
<p>16</p> <p>Stecker in den Grundkörper einsetzen / apply plug into carrier</p> <p>Hutmutter aufsetzen / tighten hat nut</p>	<p>17 dabei Rasthaken niederdrücken / in doing so press latch</p>	<p>18 max. Drehmoment 3 Nm / max. torque 3 Nm</p>										
<p>19 Optional Verriegelungsklammer / Optional Locking clasp</p> <table border="0"> <tr> <td>grau / grey</td> <td>130906-V3-I</td> </tr> <tr> <td>rot / red</td> <td>130906-V8-I</td> </tr> <tr> <td>blau / blue</td> <td>130906-V6-I</td> </tr> <tr> <td>gelb / yellow</td> <td>130906-V5-I</td> </tr> <tr> <td>grün / green</td> <td>130906-V7-I</td> </tr> </table>	grau / grey	130906-V3-I	rot / red	130906-V8-I	blau / blue	130906-V6-I	gelb / yellow	130906-V5-I	grün / green	130906-V7-I	<p>20 einsetzen / plug-in</p> <p>Anschlussdose / outlet 1309410003-E</p>	<p>21</p>
grau / grey	130906-V3-I											
rot / red	130906-V8-I											
blau / blue	130906-V6-I											
gelb / yellow	130906-V5-I											
grün / green	130906-V7-I											
<p>22</p> <p>Verriegelungsklammer schließen / close locking clasp</p>	<p>23</p> <p>Verriegelungsklammer lösen / Release locking clasp</p>	<p>24 lösen / unplug</p>										